

## County Surveyor's Record, Douglas County, Oregon

Resurvey of Sixth Standard Parallel South through Range 3 E.

CHAINS

from which

A fir, 9 ins. diam., bears S.64°E., 57 lks. dist.

Marked C C T 28 S R 3 E S 3 B T.

A fir, 14 ins. diam., bears S.12½°W., 41 lks. dist.

Marked C C T 28 S R 3 E S 4 B T.

Asc. 25 ft. over SW. slope to

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in ground, to bed rock, and raise a mound of stone, 2 ft. base, 1 ft. high, around the post, for standard cor. of secs. 33 and 34, with brass cap marked

S C  
 T 27 S R 3 E  
 S 33 S 34  
 T 28 S R 3 E  
 S 3  
 1929

from which

A fir, 5 ins. diam., bears N.37°E., 21 lks. dist.

Marked S C T 27 S R 3 E S 34 B T.

A fir, 6 ins. diam., bears N.40°W., 22 lks. dist.

Marked S C T 27 S R 3 E S 33 B T.

Land, mountainous.

Soil, sandy, gravelly, and rocky, third rate.

Timber, fir, pine, hemlock, larch, and cedar.

Undergrowth, vine maple, alder, willow, small fir,

pine, hemlock, and larch.

East, on S. bdy. of sec. 34.

Asc. 105 ft. over NW. slope, through medium timber and medium undergrowth.

5.75 Spur, slopes N., desc. 60 ft. over NE. slope.

10.59 Creek, 5 lks. wide, course NW., asc. 845 ft. over W. slope to ¼ sec. cor. of sec. 3.

25.13 Old standard ¼ sec. cor. of sec. 34, bears N., 3.84 chs. dist.

Now obliterated.

34.68 Mid point bet. NE. and NW. corners of sec. 3, determined