

Resurvey of Sixth Standard Parallel South through Range 3 E.

CHAINS

as hereinafter described.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 3 only, with brass cap marked

$\frac{1}{4}$ S 3
1929

from which

A fir, 10 ins. diam., bears S.84*E., 68 lks. dist.

Marked $\frac{1}{4}$ S 3 B T.

A larch, 14 ins. diam., bears S.53*E., 28 lks.

Marked $\frac{1}{4}$ S 3 B T.

Asc. 75 ft. over W. slope to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for standard $\frac{1}{4}$ sec. cor. of sec. 34, with brass cap marked

S C
 $\frac{1}{4}$ S 34
1929

from which

A larch, 8 ins. diam., bears N.6*E., 40 lks. dist.

Marked S C $\frac{1}{4}$ S 34 B T.

A larch, 22 ins. diam., bears N.70*W., 8 lks. dist.

Marked S C $\frac{1}{4}$ S 34 B T.

Asc. 65 ft. over NW. slope.

50.50 Trail, bears NW. and SE. and spur, slopes NW.; desc. 415 ft. over NE. slope to C C.

64.64 Old standard cor. of secs. 34 and 35, bears N., 4.12 chs. dist.

Now obliterated.

74.52 Point of intersection of the line bet. secs. 2 and 3, determined as hereinafter described.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in ground, for closing cor. of secs. 2 and 3, with brass cap marked