

County Surveyor's Record, Douglas County, Oregon

Resurvey of Sixth Standard Parallel South through Range 3 E.

CHAINS

T 27 S R 3 E  
   S 34  
   S 3 S 2  
 T 28 S R 3 E  
   C C  
 1929

from which

A larch, 16 ins. diam., bears S.35\*E., 59 lks.

Marked C C T 28 S R 3 E S 2 B T.

A larch, 20 ins. diam., bears S.58\*W., 47 lks.

Marked C C T 28 S R 3 E S 3 B T.

Desc. 55 ft. over NE. slope to

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in ground, for standard cor. of secs. 34 and 35, with brass cap marked

  S C  
 T 27 S R 3 E  
   S 34 S 35  
 T 28 S R 3 E  
   S 2  
 1929

from which

A larch, 10 ins. diam., bears N.71\*E., 21 lks. dist.

Marked S C T 27 S R 3 E S 35 B T.

A larch, 24 ins. diam., bears N.30\*W., 23 lks. dist.

Marked S C T 27 S R 3 E S 34 B T.

Land, mountainous.

Soil, sandy, gravelly, and rocky, 3rd. rate.

Timber, fir, pine, and hemlock.

Undergrowth, vine maple, huckleberry, alder, willow, small fir, pine, and hemlock.

East, on S. bdy. of sec. 35.

Desc. 180 ft. over NE. slope, through heavy timber and medium undergrowth.

10.48

Spring branch, 2 lks. wide, course NE.

20.00

Foot of desc. on N. slope; asc. 90 ft. over NW. slope to 1/4 sec. cor. of sec. 2 only.