

Resurvey of Sixth Standard Parallel South through Range 3 E.

CHAINS 25.26	Trail, bears NW. and S.
25.37	Old stand. $\frac{1}{4}$ sec. cor. of sec. 35, bears N., 3.48 chs. dist. Now obliterated.
34.69	Mid point bet. NE. and NW. corners of sec. 2, determined as hereinafter described. Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to bed rock, and raise a mound of stone, 2 ft. base, 1 ft. high, around the post, for $\frac{1}{4}$ sec. cor. of sec. 2 only, with brass cap marked $\frac{1}{4} \text{ S } 2$ 1929 from which A hemlock, 16 ins. diam., bears South, 9 lks. dist. Marked $\frac{1}{4}$ S 2 B T. A fir, 36 ins. diam., bears S.64*W., 58 lks. dist. Marked $\frac{1}{4}$ S 2 B T. Asc. 20 ft. over NW. slope to
40.00	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for standard $\frac{1}{4}$ sec. cor. of sec. 35, with brass cap marked S C $\frac{1}{4} \text{ S } 35$ 1929 from which A fir, 28 ins. diam., bears N.43*E., 26 lks. dist. Marked S C $\frac{1}{4}$ S 35 B T. A fir, 14 ins. diam., bears N.2*W., 27 lks. dist. Marked S C $\frac{1}{4}$ S 35 B T. Asc. 205 ft. over NW. slope.
65.95	Old stand. cor. of secs. 35 and 36, bears N., 4.02 chs. dist.
73.00	Ridge, bears NE. and SW., desc. slightly to
74.86	Point of intersection of the line bet. secs. 1 and 2, determined as hereinafter described. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for closing cor. of secs. 1 and 2, with brass cap marked