

County Surveyor's Record, Douglas County, Oregon

Resurvey of Sixth Standard Parallel South through Range 3 E.

CHAINS

T 27 S R 3 E  
 $\frac{S 35}{S 2 | S 1}$   
 T 28 S R 3 E  
 C C  
 1929

from which

A fir, 8 ins. diam., bears S.18 $\frac{1}{2}$ \*E., 44 lks. dist.

Marked C C T 28 S R 3 E S 1 B T.

A fir, 42 ins. diam., bears S.58\*W., 49 lks. dist.

Marked C C T 28 S R 3 E S 2 B T.

Desc. 75 ft. over SE. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in ground, for standard cor. of sec. 35 and 36, with brass cap marked

$\frac{S C}{T 27 S R 3 E}$   
 $\frac{S 35 | S 36}{T 28 S R 3 E}$   
 $\frac{S 1}{1929}$

from which

A fir, 10 ins. diam., bears N.48\*E., 15 lks. dist.

Marked S C T 27 S R 3 E S 36 B T.

A fir, 14 ins. diam., bears N.2 $\frac{1}{2}$ \*W., 123 lks. dist.

Marked S C T 27 S R 3 E S 35 B T.

Land, mountainous.

Soil, sandy, gravelly, and rocky, third rate.

Timber, fir, pine, hemlock, and cedar.

Undergrowth, huckleberry, alder, vine maple, small fir, pine, and hemlock.

East, on S. bdy. of sec. 36.

Desc. 575 ft. over SE. slope to  $\frac{1}{4}$  sec. cor. of sec. 1, through heavy timber and dense undergrowth.

26.05 Old stand.  $\frac{1}{4}$  sec. cor. of sec. 36, bears N. 4.21 chs. dist.

35.10 Mid point bet. NE. and NW. corners of sec. 1, determined as hereinafter described.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 1 only, with brass cap marked