

Resurvey of Sixth Standard Parallel South through Range 3 E.

CHAINS

1/4 S 1
1929

from which

A fir, 36 ins. diam., bears S.52*E., 78 lks. dist.

Marked 1/4 S 1 B T.

A fir, 24 ins. diam., bears S.60*W., 90 lks. dist.

Marked 1/4 S 1 B T.

Desc. 175 ft. over SE. slope to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for standard 1/4 sec. cor. of sec. 36, with brass cap marked

S C
1/4 S 36
1929

from which

A fir, 40 ins. diam., bears N.37*E., 94 lks. dist.

Marked S C 1/4 S 36 B T.

A fir, 36 ins. diam., bears N.10*W., 36 lks. dist.

Marked S C 1/4 S 36 B T.

Descend 100 ft. over SE. slope.

44.70 Creek, 3 lks. wide, course NE., asc. 140 ft. over NW. slope.

59.60 Spur, slopes NE., desc. 430 ft. over E. slope to C C.

65.65 Old standard cor. of Ts. 27 S., Rs. 3 and 4 E., bears N., 4.29 chs. dist.

Now obliterated.

75.34 Point of intersection of the line bet. Ts. 28 S., Rs. 3 and 4 E., determined as hereinafter described.

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, for closing cor. of Ts. 28 S., Rs. 3 and 4 E., with brass cap marked

T 27 S R 3 E S 36
S 1 S 6
R 3 E R 4 E
T 28 S
C C
1929

from which