

County Surveyor's Record, Douglas County, Oregon

Resurvey of Sixth Standard Parallel South through Range 3 E.

CHAINS	
80.00	<p>A fir, 36 ins. diam., bears S.67$\frac{1}{2}$*E., 71 lks. dist. Marked C C T 28 S R 4 E S 6 B T.</p> <p>A fir, 44 ins. diam., bears S.17*W., 8 lks. dist. Marked C C T 28 S R 3 E S 1 B T.</p> <p>Desc. 140 ft. over E. slope to</p> <p>Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in ground, for standard cor. of Ts. 27 S., Rs. 3 and 4 E., with brass cap marked</p> <div style="text-align: center;"> <p>S C T 27 S R 3 E R 4 E S 36 S 31 T 28 S R 4 E S 6 1929</p> </div> <p>from which</p> <p>A fir, 34 ins. diam., bears N.59*E., 23 lks. dist. Marked S C T 27 S R 4 E S 31 B T.</p> <p>A fir, 34 ins. diam., bears N.31*W., 63 lks. dist. Marked S C T 27 S R 3 E S 36 B T.</p> <p>Land, mountainous.</p> <p>Soil, sandy, gravelly, and rocky, third rate.</p> <p>Timber, fir, pine, hemlock, larch, and cedar.</p> <p>Undergrowth, rhododendron, huckleberry, hazel, alder, small fir, pine, and hemlock.</p>
14.28	<p style="text-align: center;"><u>East Boundary.</u></p> <p>From the cor. of Ts. 28 and 29 S., Rs. 3 and 4 E., which is an iron post, 3 ins. diam., set with only the top showing in a mound of stone, with brass cap marked and witnessed as described in the field notes of T. 29 S., R. 3 E.</p> <p>North, bet. secs. 31 and 36.</p> <p>Asc. 510 ft. over broken SE. slope, through scattering timber and medium undergrowth.</p>
27.40	<p>Creek, 4 lks. wide, course SE., continue asc.</p>
32.90	<p>Ridge, bears NE. and W., desc. 65 ft. over NW. slope.</p>
	<p>Draw, drains NW., asc. 60 ft. over SW. slope to</p>