

County Surveyor's Record, Douglas County, Oregon

Township 28 South, Range 3 East
East Boundary.

CHAINS

A fir, 14 ins. diam., bears N.88*W., 21 lks. dist.

Marked $\frac{1}{4}$ S 12 B T.

Desc. 300 ft. over rolling NE. slope to sec. cor.

69.40 Way trail, bears NE. and SW.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 1, 6, 7, and 12, with brass cap marked

T 28 S
R 3 E | R 4 E
S 1 | S 6
S 12 | S 7
1928

from which

A fir, 12 ins. diam., bears N.42*E., 76 lks. dist.

Marked T 28 S R 4 E S 6 B T.

A pine, 8 ins. diam., bears S.80*E., 64 lks. dist.

Marked T 28 S R 4 E S 7 B T.

A pine, 8 ins. diam., bears S.50*W., 21 lks. dist.

Marked T 28 S R 3 E S 12 B T.

A fir, 10 ins. diam., bears N.18 $\frac{1}{2}$ *W., 61 lks. dist.

Marked T 28 S R 3 E S 1 B T.

Land, mountainous and rolling mountainous.

Soil, gravelly, third rate.

Timber, fir, pine, and larch.

Undergrowth, huckleberry, alder, willow, manzanita,

and small yew.

North, bet. secs. 1 and 6.

Desc. 320 ft. over N. slope, through small timber and dense undergrowth.

19.30 Black Rock Creek, 35 lks. wide, course NE., asc. 240 ft. over SE. slope to $\frac{1}{4}$ sec. cor., through medium timber and medium undergrowth.

23.35 Trail, bears NE. and SW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked