

County Surveyor's Record, Douglas County, Oregon

Township 28 South, Range 3 East.
Subdivision.

CHAINS

Desc. 530 ft. over broken NE. slope, through stunted
timber and light undergrowth.

15.84 Creek, 3 lks. wide, course NW., desc. 40 ft. over NW.
slope.

20.19 Creek, 4 lks. wide, course NW., asc. 15 ft. over SW.
slope.

23.20 Spur, slopes NW., desc. 265 ft. over N. slope to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in
ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 35 \text{ | S } 36 \\ | \\ 1928 \end{array}$$

from which

A twin fir, 36 ins. diam., bears S.20*E., 73 lks.

Marked $\frac{1}{4}$ S 36 B T.

A fir, 20 ins. diam., bears N.42*W., 189 lks.

Marked $\frac{1}{4}$ S 35 B T.

Desc. 125 ft. over N. slope.

49.37 Fish Creek, 3 lks. wide, course E., thence over E. slope.

51.72 Trail, bears NE. and SW.

72.60 Trail, bears E. and W.

73.62 Creek, 3 lks. wide, course E., asc. 185 ft. over S. slope
to sec. cor.

77.83 Trail, bears NE. and SW.

79.19 Trail, bears NW. and SE.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the
ground, for cor. of secs. 25, 26, 35 and 36, with
brass cap marked

$$\begin{array}{c} \text{T } 28 \text{ S | R } 3 \text{ E} \\ \text{S } 26 \text{ | S } 25 \\ \hline \text{S } 35 \text{ | S } 36 \\ 1928 \end{array}$$

from which

A fir, 10 ins. diam., bears N.84*E., 55 lks. dist.

Marked T 28 S R 3 E S 25 B T.