

County Surveyor's Record, Douglas County, Oregon

Township 28th South, Range 3 East.
Subdivision.

CHAINS

NW. slope.

50.04 Trail, bears NW. and SE.
68.20 Foot of desc. on N. slope. asc. 75 ft. over NE. slope.
77.60 Rock spur, slopes NE., thence over broken N. slope to
79.82 The cor. of secs. 23, 24, 25, and 26.

Land, mountainous.

Soil, rocky and gravelly, third rate.

Timber, fir, larch, and pine.

Undergrowth, snow brush and huckleberry.

N.0°01'W., bet. secs. 23 and 24.

Desc. 440 ft. over broken NE. slope to $\frac{1}{4}$ sec. cor.,
through scattering timber and medium undergrowth.

15.85 Trail, bears E. and W.

25.26 Creek, 2 lks. wide, course NE.

31.01 Creek, 2 lks. wide, course NE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 23 \text{ | } \text{S } 24 \\ \frac{1}{4} \end{array}$$

1928

from which

A fir, 6 ins. diam., bears N.80°E., 23 lks. dist.

Marked $\frac{1}{4}$ S 24 B T.

A fir, 36 ins. diam., bears S.16°W., 41 lks. dist.

Marked $\frac{1}{4}$ S 23 B T.

Desc. 105 ft. over NE. slope.

49.84 Creek, 3 lks. wide, course E., asc. 160 ft. over SE.
slope.

62.10 Spur, slopes E., desc. 60 ft. over NE. slope.

69.45 Foot of desc. on E. slope, asc. 90 ft. over SE. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in
the ground, for cor. of secs. 13, 14, 23 and 24,
with brass cap marked