

County Surveyor's Record, Douglas County, Oregon

Township 28 South, Range 3 East.
Subdivision.

CHAINS	
	<p>A fir, 12 ins. diam., bears N.5*W., 22 lks. dist. Marked $\frac{1}{4}$ S 13 B T. Desc. 405 ft. over W. slope. 57.55 Creek, 6 lks. wide, course NW. 58.35 Quartz Creek, 10 lks. wide, course N., asc. 610 ft. over E. slope to 79.90 The cor. of secs. 13, 14, 23 and 24. Land, mountainous. Soil, sandy, gravelly, and rocky, 2nd and 3rd rate. Timber, fir, pine, and larch. Undergrowth, willow, alder, huckleberry, small fir, pine, and larch.</p>
	<p>N.0*01'W., bet. secs. 13 and 14. Asc. 35 ft. over SE. slope, through medium timber and medium undergrowth. 4.50 Spur, slopes E., desc. 95 ft. over NE. slope. 16.05 Draw, drains E., asc. 185 ft. over SE. slope to $\frac{1}{4}$ sec. cor., through patches of dense undergrowth. 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for $\frac{1}{4}$ sec. cor., with brass cap marked</p> <p style="text-align: center;"> $\frac{1}{4}$ S 14 S 13 1928</p> <p>from which</p> <p>A fir, 5 ins. diam., bears S.43*E., 18 lks. dist. Marked $\frac{1}{4}$ S 13 B T. A pine, 5 ins. diam., bears West, 75 lks. dist. Marked $\frac{1}{4}$ S 14 B T. Asc. 60 ft. over SE. slope in dense 2nd growth. 49.50 Spur, slopes E., desc. 930 ft. over broken NE. slope. 77.30 Spring branch, 1 lk. wide, course NE., continue desc. to 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in ground, for cor. of secs. 11, 12, 13, 14, with brass cap marked</p>