

County Surveyor's Record, Douglas County, Oregon

Township 28 South, Range 3 East.
Subdivision.

CHAINS	<p>over SE. slope to $\frac{1}{4}$ sec. cor.</p>
25.03	Trail, bears NE; and SW.
39.99	<p>Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked</p> $\begin{array}{c} S 1 \\ \frac{1}{4} \\ \hline S 12 \\ 1928 \end{array}$ <p>from which</p> <p>A fir, 42 ins. diam., bears S.22*W., 70 lks. dist. Marked $\frac{1}{4}$ S 12 B T.</p> <p>A fir, 36 ins. diam., bears N.25*W., 28 lks. dist. Marked $\frac{1}{4}$ S 1 B T.</p> <p>Asc. 950 ft. over broken SE. slope to sec. cor.</p>
61.58	Spring branch, 2 lks. wide, course SE.
79.98	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, mountainous.</p> <p>Soil, sandy, gravelly, and rocky, third rate.</p> <p>Timber, fir, pine, and larch.</p> <p>Undergrowth, snow brush, huckleberry, vine maple, small fir, pine, and larch.</p>
21.40	<p>N.0*01'W., bet. secs. 1 and 2.</p> <p>Asc. 500 ft. over S. slope, through medium timber and dense undergrowth.</p> <p>Trail and top of a ridge, bears NE. and SW., desc. 370 ft. over N. slope to $\frac{1}{4}$ sec. cor., enter heavy open timber, bears NE. and SW.</p>
40.00	<p>Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked</p> $\begin{array}{c} \frac{1}{4} \\ S 2 S 1 \\ 1929 \end{array}$ <p>from which</p> <p>A pine, 22 ins. diam., bears N.89*E., 26 lks. dist. Marked $\frac{1}{4}$ S 1 B T.</p>