

Township 28 South, Range 3 East.
Subdivision.

CHAINS

N.0°02'W., bet. secs. 26 and 27.

Asc. 195 ft. over S. slope, through heavy timber and
light undergrowth.

8.50 Spur, slopes W., desc. slightly to

10.65 Trail, bears E. and W., desc. 615 ft. over NW. slope to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in
ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

	↑	
S 27		S 26
1928		

from which

A hemlock, 11 ins. diam., bears N.73°E., 47 lks.

Marked $\frac{1}{4}$ S 26 B T.

A fir, 18 ins. diam., bears N.56°W., 17 lks. dist.

Marked $\frac{1}{4}$ S 27 B T.

Desc. 140 ft. over N. slope.

43.50 Creek, 5 lks. wide, course NW., asc. 45 ft. over rocky SW.
slope.

45.20 Rock spur, slopes W., desc. 80 ft. over rocky NW. slope.

47.25 Creek, 6 lks. wide, course W., asc. 950 ft. over broken
SW. slope to80.00 Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in
the ground, to bed rock, and raise a mound of stone,
4 ft. base, 2 ft. high, around the post, for cor. of
secs. 22, 23, 26 and 27, with brass cap marked

	T 28	S R 3	E
	S 22	S 23	
	S 27	S 26	
1928			

from which

A fir, 36 ins. diam., bears N.52°E., 75 lks. dist.

Marked T 28 S R 3 E S 23 B T.

A fir, 7 ins. diam., bears S.28°E., 29 lks. dist.

Marked T 28 S R 3 E S 26 B T.

A fir, 14 ins. diam., bears S.37°W., 76 lks. dist.

Marked T 28 S R 3 E S 27 B T.