

County Surveyor's Record, Douglas County, Oregon

Township 28 South, Range 3 East.
Subdivision.

CHAINS

- 20.56 Creek, 6 lks. wide, course N., asc. 35 ft. over E. slope.
- 22.00 Spur, slopes NE., desc. 20 ft. NW. slope.
- 25.30 Draw, drains NE., asc. 160 ft. over NE. slope to
- 40.21 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
- S 11
 $\frac{1}{4}$ —
S 14
1928
- from which
- A fir, 14 ins. diam., bears N.14*W., 37 lks. dist.
Marked $\frac{1}{4}$ S 11 B T.
- A larch, 12 ins. diam., bears S.77*W., 66 lks. dist.
Marked $\frac{1}{4}$ S 14 B T.
- Asc. 50 ft. over E. slope.
- 44.00 Spur, slopes N., desc. 185 ft. over NW. slope.
- 61.20 Trail, bears N. and S.
- 63.55 Creek, 7 lks. wide, course NE., asc. 210 ft. over E. slope
to
- 80.42 The cor. of secs. 10, 11, 14, and 15.
Land, mountainous and rolling.
Soil, sandy, gravelly, rocky, and peat, 2nd to 4th rate.
Timber, fir, pine, larch, hemlock, and cedar.
Undergrowth, willow, alder, huckleberry, small fir,
hemlock, and yew.
-
- N.0*02'W., bet. secs. 10 and 11.
Desc. 20 ft. over NE. slope, through medium timber and
dense undergrowth.
- 3.11 Creek, 2 lks. wide, course SE., asc. 320 ft. over SE.
slope.
- 20.00 Rocky spur, slopes SE., desc. 700 ft. over NE. slope,
cliffs and slide rock to
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in
the ground, to bed rock, and raise a mound of stone,
2 ft. base, 1 ft. high, around the post, for $\frac{1}{4}$ sec.
cor., with brass cap marked