

Township 28 South, Range 3 East.
Subdivision.

CHAINS	
	N.0*03'W., bet. secs. 32 and 33.
	Asc. 805 ft. over broken rocky SE. slope, through stunted timber and medium undergrowth.
21.50	Rock spur, slopes SW., asc. 240 ft. over broken SW. slope, enter medium timber.
37.50	Ridge and way trail, bears E. and W., desc. 40 ft. over N. slope to
40.00	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ S 32 S 33 1928
	from which
	A fir, 18 ins. diam., bears N.84*E., 47 lks. dist. Marked $\frac{1}{4}$ S 33 B T.
	A fir, 20 ins. diam., bears S.80*W., 54 lks. dist. Marked $\frac{1}{4}$ S 32 B T.
	Desc. 320 ft. over NW. slope.
57.25	Wash, 5 lks. wide, drains NW., continue desc.
61.20	Wash, 5 lks. wide, drains W., asc. 60 ft. over SW. slope.
73.20	Spur, slopes W., desc. 30 ft. over NW. slope.
76.10	Draw, drains W., asc. 65 ft. over SW. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 28, 29, 32, and 33, with brass cap marked
	T 28 S R 3 E S 29 S 28 S 32 S 33 1928
	from which
	A fir, 24 ins. diam., bears N.42*E., 39 lks. dist. Marked T 28 S R 3 E S 28 B T.
	A fir, 42 ins. diam., bears S.41*E., 20 lks. dist. Marked T 28 S R 3 E S 33 B T.
	A fir, 18 ins. diam., bears S.33*W., 53 lks. dist. Marked T 28 S R 3 E S 32 B T.
	A fir, 10 ins. diam., bears N.34*W., 58 lks. dist. Marked T 28 S R 3 E S 29 B T.