

County Surveyor's Record, Douglas County, Oregon

Township 28 South, Range 3 East.  
Subdivision.

CHAINS

from which

A fir, 8 ins. diam., bears N.32\*E., 25 lks. dist.

Marked T 28 S R 3 E S 16 B T.

A fir, 24 ins. diam., bears S.50\*E., 44 lks. dist.

Marked T 28 S R 3 E S 21 B T.

A fir, 10 ins. diam., bears S.9\*W., 16 lks. dist.

Marked T 28 S R 3 E S 20 B T.

A fir, 26 ins. diam., bears N.51\*W., 21 lks. dist.

Marked T 28 S R 3 E S 17 B T.

Land, mountainous.

Soil, sandy, gravelly, and rocky, 3rd rate.

Timber, fir, pine, hemlock, and larch.

Undergrowth, huckleberry, vine maple, small fir, and pine.

N.89\*46'E., on a random line, bet. secs. 16 and 21.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.62 Intersect N. and S. line, 5 lks. N. of the cor. of secs.  
15, 16, 21, and 22.

Thence

S.89\*48'W., on a true line.

Desc. 215 ft. over SW. slope, through an old burn,  
partly dead heavy timber and light undergrowth.

10.00 Spur, slopes SW., enter green timber, bears N. and S.,  
desc. 720 ft. over broken rocky NW. slope, almost  
impassable in several places.

35.90 Creek, 6 lks. wide, course SW., asc. 35 ft. over SE. slope to

39.81 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S 16  
 $\frac{1}{4}$  —————  
S 21  
1928

from which

A fir, 44 ins. diam., bears N.33\*E., 53 lks. dist.

Marked  $\frac{1}{4}$  S 16 B T.