

County Surveyor's Record, Douglas County, Oregon

Township 28 South, Range 3 East.
Subdivision.

CHAINS

N.0°03'W., bet. secs. 4 and 5.

Desc. 20 ft. over NW. slope, through heavy timber and dense undergrowth.

1.20 Spur, slopes NW., leave heavy timber, bears NW. and SE., desc. 570 ft. over NE. slope, through scattering stunted timber and very dense undergrowth.

18.20 Creek, 5 lks. wide, course NW., asc. 565 ft. over broken SW. slope, through light undergrowth.

34.60 Rocky spur, bears SW., desc. 50 ft. over NW. slope to $\frac{1}{4}$ sec. cor., enter medium timber, bears E. and W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ | \\ S\ 5\ | \ S\ 4 \\ | \\ 1929 \end{array}$$

from which

A fir, 12 ins. diam., bears N.86°E., 54 lks. dist.
Marked $\frac{1}{4}$ S 4 B T.

A fir, 20 ins. diam., bears S.55°W., 30 lks. dist.
Marked $\frac{1}{4}$ S 5 B T.

Asc. 110 ft. over SW. slope.

45.00 Rock pinnacle, 100 ft. high, on W. slope; desc. 265 ft. over NW. slope.

53.50 Draw, drains W., asc. 110 ft. over SW. slope.

60.00 Spur, slopes W., desc. 15 ft. over NW. slope.

64.52 Spring branch, 2 lks. wide, course W., asc. 35 ft. over SW. slope.

66.40 Spur, slopes W., desc. 35 ft. over NW. slope.

71.13 Creek, 4 lks. wide, course SW., asc. 45 ft. over SW. slope to

74.94 Intersect the 6th Standard Parallel South, at the closing cor. of secs. 4 and 5, which bears West, 5.15 chs. dist., from the standard cor. of secs. 32 and 33, and is hereinbefore described.

Land, mountainous.