

## County Surveyor's Record, Douglas County, Oregon

Township 28 South, Range 3 East.  
Subdivision.

CHAINS	
	<p>from which</p> <p>A pine, 30 ins. diam., bears N.44*E., 51 lks. dist. Marked T 28 S R 3 E S 29 B T.</p> <p>A fir, 30 ins. diam., bears S.27*E., 41 lks. dist. Marked T 28 S R 3 E S 32 B T.</p> <p>A fir, 36 ins. diam., bears S.42*W., 34 lks. dist. Marked T 28 S R 3 E S 31 B T.</p> <p>A fir, 24 ins. diam., bears N.76*W., 29 lks. dist. Marked T 28 S R 3 E S 30 B T.</p> <p>Land, mountainous.</p> <p>Soil, gravelly, and rocky, 3rd rate.</p> <p>Timber, fir, pine, and hemlock.</p> <p>Undergrowth, mountain laurel, huckleberry, rhododendron, vine maple, small fir, pine, and hemlock.</p>
40.00	N.89*54'E., on a random line, bet. secs. 29 and 32. Set temp. $\frac{1}{4}$ sec. cor.
80.20	Intersect N. and S. line, 23 lks. S. of the cor. of secs. 28, 29, 32, and 33.
	Thence
	S.89*44'W., on a true line.
	Desc. 560 ft. over SW. slope, through heavy timber and light undergrowth.
22.70	Creek, 5 lks. wide, course NW., desc. 75 ft. over NW. slope.
26.30	Foot of desc. on N. slope; asc. 30 ft. over NE. slope.
31.25	Spur, slopes NW., desc. 80 ft. over NW. slope to
40.10	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, to bed rock, and raise a mound of stone, 4 ft. base, 2 ft. high, around the post, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \begin{array}{r} S 29 \\ \hline S 32 \\ 1929 \end{array}$
	from which