

## County Surveyor's Record, Douglas County, Oregon

Township 28 South, Range 3 East.  
Subdivision.

CHAINS	
39.93	<p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., with brass cap marked</p> <p style="text-align: center;"> <math display="block">\begin{array}{r} S\ 20 \\ \frac{1}{4} \\ \hline S\ 29 \\ 1929 \end{array}</math> </p> <p>from which</p> <p style="padding-left: 40px;">A pine, 28 ins. diam., bears S.52*E., 9 lks. dist. Marked <math>\frac{1}{4}</math> S 29 B T.</p> <p style="padding-left: 40px;">A pine, 28 ins. diam., bears N.20*W., 33 lks. dist. Marked <math>\frac{1}{4}</math> S 20 B T.</p> <p>Asc. 60 ft. over NE. slope.</p>
47.00	Spur, slopes N., desc. 350 ft. over NW. slope.
59.45	Draw, drains NW., asc. 15 ft. over NE. slope.
65.00	Spur, slopes N., desc. 335 ft. over NW. slope to
79.86	The cor. of secs. 19, 20, 29, and 30.
	<p>Land, mountainous.</p> <p>Soil, sandy, gravelly, and rocky, 2nd to 3rd rate.</p> <p>Timber, fir, pine, hemlock, and larch.</p> <p>Undergrowth, rhododendron and vine maple.</p>
	S.89*58'W., on a random line, bet. secs. 19 and 30.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
82.18	<p>Intersedt W. bdy. of Tp. 38 lks. S. of the cor. of secs. 19, 24, 25, and 30.</p> <p>Thence</p> <p>S.89*46'E., on a true line.</p> <p>Desc. 60 ft. over SE. slope, through medium timber and dense undergrowth.</p>
3.80	<p>Castle Rock Creek, 30 lks. wide, course SW., asc. 1100 ft. over broken NW. slope to</p>
42.18	<p>Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., with brass cap marked.</p> <p style="text-align: center;"> <math display="block">\begin{array}{r} S\ 19. \\ \frac{1}{4} \\ \hline S\ 30 \\ 1929 \end{array}</math> </p> <p>from which</p>