

## County Surveyor's Record, Douglas County, Oregon

Township 28 South, Range 3 East.  
Subdivision.

CHAINS

T 28 S | R 3 E  
S 18 | S 17  
S 19 | S 20  
1929

from which

A fir, 36 ins. diam., bears N.38\*E., 47 lks. dist.

Marked T 28 S R 3 E S 17 B T.

A fir, 16 ins. diam., bears S.50\*E., 32 lks. dist.

Marked T 28 S R 3 E S. 20 B T.

A fir, 14 ins. diam., bears S.41\*W., 30 lks. dist.

Marked T 28 S R 3 E S. 19 B T.

A fir, 16 ins. diam., bears N.62\*W., 9 lks. dist.

Marked T 28 S R 3 E S 18 B T.

Land, mountainous.

Soil, sandy, gravelly, and rocky, 3rd rate.

Timber, fir, pine, hemlock, and cedar.

Undergrowth, thododendron, vine maple, hazel, alder,

willow, small fir, pine, and hemlock.

N.89\*49'E., on a random line, bet. secs. 17 and 20.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.96 Intersect N. and S. line, 12 lks. S. of the cor. of secs.  
16, 17, 20, and 21.

Thence

S.89\*44'W., on a true line.

Asc. 140 ft. over NE. slope, through medium timber and  
dense undergrowth.

.5.00 Spur, slopes N., thence over N. slope.

9.90 Spur, slopes N., desc. 280 ft. over NW. slope.

18.16 Creek, 2 lks. wide, course NW.

18.71 Creek, 2 lks. wide, course NW., asc. 90 ft. over NE. slope.

30.00 Spur, slopes NW., desc. 330 ft. over NW. slope to  $\frac{1}{4}$  sec.  
cor.

31.20 Way trail, bears NW. and SE.

39.98 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in  
the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked