

County Surveyor's Record, Douglas County, Oregon

Township 28 South, Range 3 East.
Subdivision.

CHAINS

60.96

Creek, 10 lks. wide, course SW., asc. 175 ft. over
broken S. slope to

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground, for cor. of secs. 5, 6, 7, and 8, with
brass cap marked

T 28 S	R 3 E
S 6	S 5
S 7	S 8
1929	

from which

A fir, 30 ins. diam., bears N.71*E., 39 lks. dist.

Marked T 28 S R 3 E S 5 B T.

A fir, 26 ins. diam., bears S.34*E., 13 lks. dist.

Marked T 28 S R 3 E S 8 B T.

A fir, 24 ins. diam., bears S.41*W., 61 lks. dist.

Marked T 28 S R 3 E S 7 B T.

A fir, 36 ins. diam., bears N.68*W., 68 lks. dist.

Marked T 28 S R 3 E S 6 B T.

Land, mountainous.

Soil, sandy, gravelly, and rocky, 2nd rate.

Timber, fir, pine, hemlock, and cedar.

Undergrowth, rhododendron, vine maple, willow, small
fir, pine, and hemlock.

N.89*56'E., on a random line, bet. secs. 5 and 8.

40.00

Set temp. $\frac{1}{4}$ sec. cor.

80.46

Intersect N. and S. line, 2 lks. S. of the cor. of secs.
4, 5, 8, and 9.

Thence

S.89*55'W., on a true line.

Desc. 900 ft. over broken NW. slope, through heavy timber
and light undergrowth, to $\frac{1}{4}$ sec. cor.

33.81

Spring branch, 1 lk. wide, course NW.

40.23

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked