

South Boundary of T. 29 S., R. 1 E.

CHAINS

- A Laurel, 6 ins. diam., bears N.30*E., 20 lks.
 A Pine, 20 ins. diam., bears S.8*W., 84 lks.
 53.00 Enter thick timber, course NW. and SE.
 75.50 A spring, bears N. about 25 lks.
 80.00 Set post, cor. Secs. 33, 34, 3 and 4, from which
 A Fir, 18 ins. diam., bears N.67*W., 10 lks.
 A Fir, 36 ins. diam., bears N.5*E., 35 lks.
 A Fir, 10 ins. diam., bears S.27*E., 35 lks.
 A Fir, 6 ins. diam., bears S.1*W., 60 lks.
 80.00 Va. 18*45'E.

Land, hilly and sloping to the East.

Timber, same as last mile.

This township is very mountainous and unfit for
 settlement.

Willamette Meridian, Through T. 29 S.,
 As surveyed by Homer D. Angell, U. S. Deputy
 Surveyor, under Contract No. 746, dated
 May 5th, 1902.

At the corner of T. 29 S., R. 1 W.

Thence I run

North, bet. Secs. 31 and 36.

Over rolling ground through heavy timber and dense
 undergrowth.

- 39.95 A spring, brach 1 lk. wide, course NE.

Difference between measurement of 40.00 chs. by two
 sets of chainmen is 10 lks.

Position of middle point by 1st set, 40.05; by 2nd set,
 39.95, the mean of which is

- 40.00 Set a Basalt stone, 15x14x4 ins., 10 ins. in ground
 for $\frac{1}{4}$ Sec. cor., marked $\frac{1}{4}$ on W. face, from which