

Willamette Meridian, Through T 29 S.,

CHAINS

- At the cor. of secs. 12 and 13,
Thence I run
North bet. secs. 7 and 12,
Over W. slope, through heavy timber and dense undergrowth.
- 16.75 Top of ridge, 750 ft. high, bears E. and W., descend.
Difference between measurement of 40.00 chs. by two
sets of chainmen is 8 lks.; position of middle point,
By 1st set, 40.04
By 2nd set, 39.96,
the mean of which is,
- 40.00 Set a basalt stone, 12x10x6 ins., 8 ins. in ground for
 $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face; from which,
A fir, 10 ins. diam., bears S.55*E., 25 lks.
dist., marked $\frac{1}{4}$ S 7 B T
A fir, 12 ins. diam., bears S.84*W., 19 lks.
dist., marked $\frac{1}{4}$ S 12 B T
- 42.00 Foot of descent.
- 42.15 A spring branch, 5 lks. wide, course W.; ascend,
hillside bears SE. and NW.
- 75.00 Top of ridge, bears E. and W.; descend.
Difference between measurement of 80.00 chs. by two
sets of chainmen is 14 lks.; position of middle point,
By 1st set, 80.07
By 2nd set, 79.93,
the mean of which is,
- 80.00 Set a basalt stone, 15x12x10 ins., 10 ins. in ground,
for cor. of secs. 1 and 12, marked with 1 notch on
N. and 5 notches on S. sides; from which,
A fir, 14 ins. diam., bears S.20*W., 18 lks.,
dist., marked T 29 S R 1 W S 12 B T
A fir, 12 ins. diam., bears N.68*W., 14 lks.
dist., marked T 29 S R 1 W S 1 B T