

County Surveyor's Record, Douglas County, Oregon

Resurvey of Willamette Meridian,

CHAINS	
	A fir, 40 ins. diam., bears N.66*W., 43 lks. dist., mkd. $\frac{1}{4}$ S 1 B T
	I obliterate marks on former bearing tree in T 30 S., R. 1 E.
	Thence I run
	North, on W. bdy. sec. 31, retracing Willamette Meridian. Over mountainous land, heavily timbered and covered with dense undergrowth.
	Desc. NE. slope.
9.00	Small swale, course E. Gradually ascend SE. slope.
16.00	Low ridge bears E. and W.
22.00	Enter Willow burn.
36.50	Low ridge bears E. and W.
36.85	Trail bears E. and W.
40.00	Set a basalt stone, 15x10x8 ins., 10 ins. in the ground, for $\frac{1}{4}$ sec.cor., on W. bdy. sec. 31, mkd. $\frac{1}{4}$ on E. face, from which, A fir, 5 ins. diam., bears N.19*E., 4 lks. dist., mkd. $\frac{1}{4}$ S 31 B T A madrone, 6 ins. diam., bears S.42*E., 48 lks. dist., mkd. $\frac{1}{4}$ S 31 B T.
40.90	Trail to Acker's bears E. and W.
42.11	A pine, 40 ins. diam., mkd. with 2 notches on N. and S. sides.
43.20	The SE. cor. of T 29 S., R 1 W., which is a basalt stone, 4x8x8 ins. above ground, firmly set, mkd. and witnessed as described by the surveyor general.
68.00	Divide bet. N. and S. Forks of South Umpqua river bears E. and W. Desc. N. slope.
80.00	Set a conglomerate stone, 18x12x6 ins., 12 ins. in the ground for cor. of secs. 30 and 31, mkd. with 5 notches on N. and 1 notch on S. edge, from which,