

Resurvey of Willamette Meridian

CHAINS

A hemlock, 9 ins. diam., bears N.44*E., 10 lks.

dist., mkd. T 29 S R 1 E S 30 B T

A hemlock, 6 ins. diam., bears S.45*E., 5 lks.

dist., mkd. T 29 S R 1 E S 31 B T

Land; mountainous.

Soil; loam and stony, 2nd and 3rd rate.

Timber; fir, pine, cedar; undergrowth, willow, arrow wood,
fir, hemlock.

Sept. 26, 1910.

At the cor. of secs. 30 and 31.

Thence I run,

North on W. bdy. sec. 30, retracing the Willamette
Meridian.

Over mountainous land, heavily timbered and covered with
dense undergrowth.

Desc. NE. slope.

3.20 The $\frac{1}{4}$ sec. cor. on E. bdy. Sec. 36, T 29 S, R 1 W, which is
a basalt stone, 5x14x4 ins..above ground, firmly set,
mkd and witnessed as described by the surveyor general.
I re-establish this cor. in its original position as the
 $\frac{1}{4}$ sec. cor. on E. bdy. sec. 36, T 29 S, R 1 W, only
as follows:

Stone already set and described, from which,

A fir, 16 ins. diam., bears S.79*W., 44 lks. dist.,

mkd. $\frac{1}{4}$ S 36 B T

A fir, 10 ins. diam., bears N.40*W., 80 lks. dist.,

mkd. $\frac{1}{4}$ S 36 B T

I obliterate marks on former bearing tree in T 29 S, R 1 E.

19.85 Ravine, course NE.

25.25 Ravine, course E.

30.10 Creek, 1 lk. wide, course NE.

40.00 Set a basalt stone, 18x10x4 ins., 12 ins. in the ground,
for $\frac{1}{4}$ sec. cor. on W. bdy. sec. 30, mkd. $\frac{1}{4}$ on E. face,
from which,