

County Surveyor's Record, Douglas County, Oregon

Resurvey of Willamette Meridian

CHAINS

A fir, 8 ins. diam., bears N.18*E., 106 lks.
dist., mkd. $\frac{1}{4}$ S 30 B T

A fir, 7 ins. diam., bears S.15*E., 12 lks.
dist., mkd. $\frac{1}{4}$ S 30 B T

43.39 The cor. of secs. 25 and 36, T 29 S., R. 1 W., which is a
basalt stone, 5x12x10 ins. above ground, firmly set,
mkd. and witnessed as described by the surveyor general.

80.00 Set a conglomerate stone, 15x8x8 ins., 10 ins. in the
ground, for cor. of secs. 19 and 30, mkd. with 4 notches
on N. and 2 notches on S. edge, from which,

A fir, 9 ins. diam., bears N.83*E., 66 lks.
dist., mkd. T 29 S R 1 E S 19 B T

A fir, 16 ins. diam., bears S.64*E., 20 lks.
dist., mkd. T 29 S R 1 E S 30 B T

From this cor. the $\frac{1}{4}$ sec. cor. on E. bdy. sec. 25, T 29 S,
R 1 W, which is a basalt stone, 5x8x6 ins. above
ground, firmly set, mkd. and witnessed as described
by the surveyor general, bears North 3.47 chs. dist.
I re-establish this cor. in its original position as the
 $\frac{1}{4}$ sec. cor. on E. bdy. sec. 25, T 29 S, R 1 W, only,
as follows:

Stone already set and described, from which,

A fir, 36 ins. diam., bears S.60*W., 38 lks. dist.,
mkd. $\frac{1}{4}$ S 25 B T

A madrone, 20 ins. diam., bears N.56*W., 6 lks. dist.,
mkd. $\frac{1}{4}$ S 25 B T

I destroy marks on former bearing tree in T 29 S, R 1 E.

Land; mountainous.

Soil; loam and stony, 2nd and 3rd rate.

Timber; fir, cedar, hemlock; undergrowth, fir, hemlock,
arrow wood, vine maple.

Sept. 27, 1910.