

County Surveyor's Record, Douglas County, Oregon

South Boundary of Tp. 29 S., R. 1 E.

CHAINS	
	<p>A fir, 24 ins. diam., bears S.18*E., 39 lks. dist., mkd. T 30 S R 1 E S 3 B T</p> <p>A fir, 16 ins. diam., bears S.30*W., 54 lks. dist., mkd. T 30 S R 1 E S 4 B T</p> <p>A fir, 7 ins. diam., bears N.12*W., 20 lks. dist., mkd. T 29 S R 1 E S 33 B T</p> <p>Land; mountainous.</p> <p>Soil; clay and stony, 2nd and 3rd rate.</p> <p>Timber; fir, pine, cedar; undergrowth, hazel, fir.</p> <p style="text-align: right;">Sept. 30, 1910.</p>
	<p>At the cor. of secs. 3, 4, 33 and 34.</p> <p>Thence I run</p> <p>East bet. secs. 3 and 34.</p> <p>Over mountainous land, heavily timbered and covered with dense undergrowth.</p> <p>Desc. SE. slope.</p>
5.20	<p>Creek, 1 lk. wide, course S.</p> <p>Asc. SW. slope of Tallow Butte.</p>
40.00	<p>Set a conglomerate stone, 15x8x4 ins., 10 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., mkd. <math>\frac{1}{4}</math> on N. face, from which,</p> <p style="padding-left: 40px;">A fir, 36 ins. diam., bears N.46*W., 19 lks. dist., mkd. <math>\frac{1}{4}</math> S 34 B T</p> <p style="padding-left: 40px;">A madrone, 12 ins. diam., bears S.44*W., 21 lks. dist., mkd. <math>\frac{1}{4}</math> S 3 B T</p>
52.25	Ridge bears N. and S.
60.00	Ravine, course S.
61.70	Ridge bears N. and S.
68.35	<p>Summit of line on S. slope of Tallow Butte.</p> <p>Desc. SE. slope.</p>
80.00	<p>Set a conglomerate stone, 18x12x6 ins., 12 ins. in the ground, for cor. of secs. 2, 3, 34 and 35, mkd. with 2 notches on E. and 4 notches on W. edge, from which,</p>