

County Surveyor's Record, Douglas County, Oregon

South Bdy. of Tp. 29 S., R. 1 E.

CHAINS

Along S. slope.

- 80.00 Set a conglomerate stone, 15x15x12 ins., 10 ins. in the ground, for cor. of secs. 1, 2, 35 and 36, mkd. with 1 notch on E. and 5 notches on W. edge, from which
- A pine, 28 ins. diam., bears N.63*E., 27 lks. dist. mkd. T 29 S R 1 E S 36 B T
- A fir, 24 ins. diam., bears S.35*E., 44 lks. dist., mkd. T 30 S R 1 E S 1 B T
- A fir, 20 ins. diam., bears S.52*W., 20 lks. dist., mkd. T 30 S R 1 E S 2 B T
- A pine, 30 ins. diam., bears N.55*W., 77 lks. dist., mkd. T 29 S R 1 E S 35 B T

Land; mountainous.

Soil; clay and stony, 2nd and 3rd rate.

Timber; fir, pine, cedar; undergrowth, hazel, vine maple, fir.

Oct. 2nd, 1910.

At the cor. of secs. 1, 2, 35 and 36.

Thence I run

East bet. secs. 1 and 36.

Over mountainous land, heavily timbered and covered with dense undergrowth.

Asc. SW. slope.

- 4.00 Ridge bears NE. and SW.

Along S. slope.

- 9.90 Trail bears NW. and SE.

- 28.60 Ravine, course S.

- 40.00 Set a basalt stone, 18x9x6 ins., 12 ins. in the ground, for $\frac{1}{4}$ sec. cor. mkd. $\frac{1}{4}$ on N. face, from which,
- A fir, 12 ins. diam., bears N.35*W., 30 lks. dist., mkd. $\frac{1}{4}$ S 36 B T
- A yew, 8 ins. diam., bears S.61*W., 27 lks. dist., mkd. $\frac{1}{4}$ S 1 B T.