

County Surveyor's Record, Douglas County, Oregon

Portion of  
East Bdy. of Tp. 29 S., R. 1 E.

CHAINS

A fir, 8 ins. diam., bears N.46\*E., 10 lks. dist.,  
mkd. 1/4 S 31 B T

A madrone, 9 ins. diam., bears S.45\*W., 15 lks. dist.,  
mkd. 1/4 S 36 B T

43.90 Creek, 2 lks. wide, course SW.

80.00 Set a basalt stone, 18x12x5 ins., 12 ins. in the ground,  
for cor. of secs. 25, 30, 31 and 36, mkd. with 5  
notches on N. and 1 notch on S. edge, from which,

A fir, 7 ins. diam., bears N.82\*E., 23 lks. dist.,  
mkd. T 29 S R 2 E S 30 B T

A fir, 10 ins. diam., bears S.70\*E., 20 lks. dist.,  
mkd. T 29 S R 2 E S 31 B T

A fir, 12 ins. diam., bears S.77\*W., 20 lks. dist.,  
mkd. T 29 B R 1 E S 36 B T

A madrone, 7 ins. diam., bears N.15\*W., 20 lks. dist.,  
mkd. T 29 S R 1 E S 25 B T

Land; mountainous.

Soil; clay and stony, 3rd and 4th rate.

Timber; fir, pine, cedar; undergrowth, hazel, fir.

October 4, 1910.

At the cor. of secs. 25, 30, 31 and 36.

Thence I run

North bet. secs. 25 and 30.

Over mountainous land, heavily timbered and covered with  
dense undergrowth.

Asc. S. slope.

13.50 Ravine, course SW.

40.00 Set a basalt stone, 15x8x6 ins., 10 ins. in the ground,  
for 1/4 sec. cor., mkd. 1/4 on W. face, from which,

A cedar, 18 ins. diam., bears N.29\*E., 24 lks. dist.,  
mkd. 1/4 S 30 B T

A cedar, 15 ins. diam., bears N.18\*W., 9 lks. dist.,  
mkd. 1/4 S 25 B T