

County Surveyor's Record, Douglas County, Oregon

Subdivision of Tp. 29 S., R. 1 E.

CHAINS	
	At the cor. of secs. 26, 27, 34 and 35.
	Thence I run
	N.0°02'W., bet. secs. 26 and 27
	Over Mountainous land, heavily timbered and covered with dense undergrowth.
1.00	Divide bet. N. and S. Forks of South Umpqua River bears E. and W.
	Desc. N. slope.
17.50	Creek, 1 lk. wide, course NW.
	Asc. SW. slope.
27.00	Ridge point descending W.
	Desc. N. slope.
35.20	Creek, 2 lks. wide, course NW.
	Asc. SW. slope.
40.00	Set a conglomerate stone, 18x12x10 ins., 12 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, from which, A cedar, 8 ins. diam., bears S.41 $\frac{1}{2}$ *E., 48 lks. dist., mkd. $\frac{1}{4}$ S 26 B T A cedar, 7 ins. diam., bears S.29*W., 17 lks. dist., mkd. $\frac{1}{4}$ S 27 B T
56.00	Ravine, course NW.
58.00	Ridge point descending NW.
	Desc. N. slope.
63.50	Creek, 2 lks. wide, course W.
80.00	Set a conglomerate stone, 15x12x8 ins., 10 ins. in the ground, for cor. of secs. 22, 23, 26 and 27, mkd. with 2 notches on S. and E. edges, from which, A fir, 18 ins. diam., bears N.40*E., 67 lks. dist., mkd. T 29 S R 1 E S 23 B T A fir, 16 ins. diam., bears S.89*E., 66 lks. dist., mkd. T 29 S R 1 E S 26 B T A fir, 36 ins. diam., bears S.59*W., 87 lks. dist., mkd. T 29 S R 1 E S 27 B T