

34
County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 1. E.,

CHAINS

At the cor. of secs. 4, 5, 32 and 33, on the S. Bdy.
of the Tp, previously described.

Thence I run
N.0*3'W., bet. secs. 32 and 33.
Over mountainous land, heavily timbered and covered with
dense undergrowth.
Gradually asc. S. slope.

11.00 Ridge bears NW. and SE.
23.50 Ridge bears NW. and SE.
25.60 Creek, 2 lks. wide, course SE.
40.00 Set a conglomerate stone, 18x10x4 ins., 12 ins. in the
ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face,
from which,
 A fir, 20 ins. diam., bears N.83*E., 43 lks.
 dist., mkd. $\frac{1}{4}$ S 33 B T
 An oak, 6 ins. diam., bears S.84*W., 16 lks.
 dist., mkd. $\frac{1}{4}$ S 32 B T

44.35 Trail to U. S. Forest station bears NW. and SE.
46.00 Trail to Acker's bears E. and W.
48.00 Divide bet. N. and S. Forks of South Umpqua river bears
 NW. and SE.
Desc. N. slope.

72.20 Creek, 1 lk. wide, course NE.
80.00 Set a conglomerate stone, 15x8x6 ins., 10 ins. in the
ground, for cor. of secs. 28, 29, 32 and 33, mkd.
with 1 notch on S. and 4 notches on E. edge, from
which,
 A yew, 9 ins. diam., bears N.23*E., 14 lks.
 dist., mkd. T 29 S R 1 E S 28 B T
 A fir, 12 ins. diam., bears S.61*E., 7 lks.
 dist., mkd. T 29 S R 1 E S 33 B T
 A hemlock, 8 ins. diam., bears S.9*W., 18 lks.
 dist., mkd. T 29 S R 1 E S 32 B T