

Retracement and Resurvey of Willamette Meridian
through T. 29 S.

CHAINS	
	Thence North, retracing E. bdy. of sec. 1, T. 29 S., R. 1 W.
39.98	Fall 19 lks. W. of the $\frac{1}{4}$ sec. cor. The bearing and length of this line, to the $\frac{1}{4}$ sec. cor., is N.0°16'E., 39.98 chs.
Resurvey of Willamette Meridian through T. 29 S.	
	From the cor. of secs. 19 and 30, on W. bdy. of T. 29 S., R. 1 E., which is a conglomerate stone, 5x8x8 ins., above ground, firmly set, marked and witnessed as des- cribed by the surveyor general, North, resurveying W. bdy. of sec. 19. Over mountainous land, through heavy timber and dense undergrowth. Along ridge, bears N. and S.
3.44	Intersect the $\frac{1}{4}$ sec. cor. on E. bdy. of sec. 25, T. 29 S., R. 1 W., which is a basalt stone, 5x8x6 ins., above ground, firmly set, marked and witnessed as described by the surveyor general. Descend 325 ft. on NE. slope.
24.00	Draw, course E.; ascend 20 ft. on SE. slope.
26.25	Rocky point, slopes E.; descend 100 ft. over bluff.
26.80	Foot of bluff; descend 350 ft. on NE. slope, to
40.10	Midpoint on W. bdy. of sec. 19. Set a basalt stone, 20x12x8 ins., 12 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 19 only, marked $\frac{1}{4}$ on E. face; from which, A fir, 7 ins. diam., bears N.48°E., 21 lks. dist., marked $\frac{1}{4}$ S 19 B T. A fir, 20 ins. diam., bears S.22°E., 15 lks. dist., marked $\frac{1}{4}$ S 19 B T. No iron post available for this corner. Descend 45 ft. on N. slope, to