

Resurvey of Willamette Meridian through T. 29 S.

CHAINS

43.57 Intersect the cor. of secs. 24 and 25, T. 29 S., R. 1 W., which is a basalt stone, 4x12x6 ins., above ground, firmly set, marked and witnessed as described by the surveyor general.

Thence N.0*12'E.

Descend 425 ft. on broken NE. slope, to spur.

3.30 Creek, 2 lks. wide, course NE.

16.20 Ravine, course NE.

30.75 Spur, slopes NE.; descend 275 ft. on NW. slope, to

36.63 Point of intersection with line bet. secs. 18 and 19, determined as hereinafter set forth.

Set a basalt stone, 20x10x10 ins., 15 ins. in the ground, for closing cor. of secs. 18 and 19, marked CC on E., with 3 grooves on N. and S. faces; from which,

A cedar, 20 ins. diam., bears N.33*E., 19 lks. dist., marked T 29 S R 1 E S 18 C C B T.

A hemlock, 6 ins. diam., bears S.50*E., 8 lks. dist., marked T 29 S R 1 E S 19 C C B T.

No iron post available for this cor.

Land, mountainous.

Soil, clay loam, 2nd and 3rd rate.

Timber, fir, pine, cedar, and hemlock.

Undergrowth, hazel, chinquapin, vine maple, fir.

N.0*12'E., resurveying W. bdy. of sec. 18.

Over level bench, through heavy timber and dense undergrowth.

3.20 Intersect $\frac{1}{4}$ sec. cor. on E. bdy. of sec. 24, T. 29 S., R. 1 W., which is a basalt stone, 4x10x8 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. I obliterate marks on bearing tree E. of line, and take new bearing tree.

From the corner,