

Resurvey of Willamette Meridian, through
T. 29 S.

CHAINS

(Old bearing tree) A fir, 24 ins. diam., bears
S.48*W., 34 lks. dist., mkd. $\frac{1}{4}$ S 24 B T

(New bearing tree) A fir, 14 ins. diam., bears
N.65*W., 51 lks. dist., mkd. $\frac{1}{4}$ S 24 B T

Thence N.0*10'E.

Descend 20 ft. to

0.75 Left bank of South Umpqua River, 100 lks. wide, course W.

1.75 Right bank of river; ascend 150 ft. on S. slope, to

5.55 Trail, Tiller To Quartz Mountain and Grasshopper Ranger
Stations, bears E. and W.; ascend 380 ft. on S. slope.

29.00 Spur, slopes SW.; descend 60 ft. on NW. slope.

32.80 Draw, course W.; ascend 40 ft. on SW. slope, to

36.69 Midpoint on W. bdy. of sec. 18.

Set a basalt stone, 20x10x8 ins., 15 ins. in the ground,
for $\frac{1}{4}$ sec. cor. of sec. 18 only, marked $\frac{1}{4}$ on E.
face; from which,

A fir, 20 ins. diam., bears N.15*E., 94 lks. dist.,
mkd. $\frac{1}{4}$ S 18 B T

A fir, 36 ins. diam., bears S.34*E., 120 lks. dist.,
mkd. $\frac{1}{4}$ S 18 B T

No iron post available for this cor.

Thence over W. slope.

40.04 Intersect the cor. of secs. 13 and 24, T. 29 S., R. 1 W.,
which is a basalt stone, 5x12x8 ins. above ground,
firmly set, marked and witnessed as described by
the surveyor general.

Thence N.0*09'E.

Asc. 75 ft. on SW. slope.

6.20 Spur, slopes SW.; descend 125 ft. on NW. slope.

11.30 Draw, course SW.; ascend 135 ft. on SE. slope.

24.00 Spur, slopes SW.; descend 80 ft. on NW. slope.

29.30 Creek, 1 lk. wide, course SW.; ascend 140 ft. on SE.
slope, to