

48  
County Surveyor's Record, Douglas County, Oregon

Resurvey of Willamette Meridian, through  
T. 29 S.,

CHAINS  36.54	<p>Point of intersection with line bet. secs. 7 and 18, determined as hereinafter set forth.</p> <p>Set a basalt stone, 20x8x6 ins., 15 ins. in the ground, for closing cor. of secs. 7 and 18, marked CC on E., with 2 grooves on N., and 4 grooves on S. face; from which</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N.58*E., 64 lks. dist., mkd. T 29 S R 1 E S 7 C C B T</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S.41*E., 41 lks. dist., mkd. T 29 S R 1 E S 18 C C B T</p> <p>No iron post available for this cor.</p> <p>Land; mountainous.</p> <p>Soil; clay loam, 2nd and 3rd rate.</p> <p>Timber; fir, cedar, pine, and hemlock.</p> <p>Undergrowth; snow brush, chinquapin, hazel, vine maple.</p>
3.45	<p>N.0*09'E., resurveying W. bdy. of sec. 7.</p> <p>Over mountainous land, through heavy timber and dense undergrowth.</p> <p>Ascend 110 ft. on S. slope, to</p> <p>Intersect the ¼ sec. cor. on E. bdy. of sec. 13, T. 29 S., R. 1 W., which is a basalt stone, 5x10x8 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. I obliterate marks on bearing tree E. of line, and take new bearing tree.</p> <p>From the cor.,</p> <p style="padding-left: 40px;">(Old bearing tree) A fir, 16 ins. diam., bears S.56*W., 30 lks. dist., mkd. ¼ S 13 B T</p> <p style="padding-left: 40px;">(New bearing tree) A madrona, 12 ins. diam., bears N.48*W., 23 lks. dist., mkd. ¼ S 13 B T</p> <p>Thence N.0*12'E.</p> <p>Ascend 160 ft. on SW. slope.</p>
9.70	<p>Spur, slopes SW.; descend 45 ft. on NW. slope.</p>