

Resurvey of Willamette Meridian, through T. 29 S.,

CHAINS

- 14.10 Creek, 2 lks. wide, course SW.; asc. 20 ft. on SW. slope,
to,
- 21.10 Old South Umpqua trail, bears NE. and SW.; asc. 360 ft.
on S. slope.
- 36.00 Spur, slopes W.; desc. 20 ft. on N. slope, to
- 36.46 Midpoint on W. bdy. of sec. 7.
Set a basalt stone, 20x10x6 ins., 12 ins. in the ground
for $\frac{1}{4}$ sec. cor. of sec. 7 only, marked $\frac{1}{4}$ on E. face;
from which,
 A fir, 30 ins. diam., bears N.77*E., 28 lks. dist.,
 mkd. $\frac{1}{4}$ S 7 B T
 A fir, 20 ins. diam., bears S.57*E., 14 lks. dist.,
 mkd. $\frac{1}{4}$ S 7 B T
No iron post available for this cor.
Desc. 160 ft. on N. slope, to
- 40.05 Intersect the cor. of secs. 12 and 13, T. 29 S., R. 1 W.,
which is a basalt stone, 5x12x10 ins. above ground,
firmly set, marked and witnessed as described by
the surveyor general.
Thence N.0*14'E.,
Desc. 160 ft. on N. slope.
- 6.10 Creek, 2 lks. wide, course W.; asc. 185 ft. on S. slope.
- 16.80 Spur, slopes SW.; desc. 280 ft. on NW. slope.
- 29.75 Spur, slopes NW.; desc. 175 ft. on NE. slope, to
- 36.32 Point of intersection with line bet. secs. 6 and 7,
determined as hereinafter set forth.
Set a conglomerate stone, 22x12x8 ins., 16 ins. in the
ground, for closing cor. of secs. 6 and 7, marked
CC on E., with 1 groove on N., and 5 grooves on S.
face; from which,
 A pine, 48 ins. diam., bears N.77*E., 139 lks.
 dist., mkd. T 29 S R 1 E S 6 C C B T