

50

County Surveyor's Record, Douglas County, Oregon

Resurvey of Willamette Meridian, through T. 29 S.,

CHAINS

A fir, 30 ins. diam., bears S.53°E., 135 lks.

dist., mkd. T 29 S R 1 E S 7 C C B T

No iron post available for this cor.

Land; mountainous.

Soil; clay loam, 2nd rate.

Timber; fir, pine, cedar, and hemlock.

Undergrowth; chinquapin, laurel, hazel, vine maple.

N.0°14'E., resurveying W. bdy. of sec. 6.

Over mountainous land, through heavy timber and dense undergrowth.

Descend 190 ft. on N. slope, to

3.66 Intersect the $\frac{1}{4}$ sec. cor. on E. bdy. of sec. 12, T. 29 S.,

R. 1 W., which is a basalt stone, 4x10x6 ins. above ground, firmly set, marked and witnessed as described by the surveyor general, except that the bearing tree E. of line is dead and fallen. I take new bearing tree.

From the corner,

(Old bearing tree) A fir, 14 ins. diam., bears S.84°W., 19 lks. dist., mkd. $\frac{1}{4}$ S 12 B T

(New bearing tree) A hemlock, 6 ins. diam., bears N.60°W., 14 lks. dist., mkd. $\frac{1}{4}$ S 12 B T

Thence N.0°12'E.,

Descend 90 ft. on N. slope.

2.10 Creek, 5 lks. wide, course NW.; asc. 80 ft. on S. slope.

5.15 Small spur, slopes SW.; desc. 20 ft. on NW. slope.

12.10 Ravine, course SW.; asc. 700 ft. on S. slope.

35.60 Spur, slopes NW.

36.34 Point 40.00 chs. N. of closing cor. of secs. 6 and 7.

Set a granite stone, 20x12x12 ins., 12 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 6 only, marked $\frac{1}{4}$ on E. face, from which,