

Resurvey of Willamette Meridian, through T. 29 S.,

CHAINS

A fir, 18 ins. diam., bears N.35\*E., 53 lks.  
dist., mkd.  $\frac{1}{4}$  S 6 B T

A fir, 20 ins. diam., bears S.30\*E., 22 lks.  
dist., mkd.  $\frac{1}{4}$  S 6 B T

No iron post available for this cor.

Desc. 20 ft. on NE. slope, to

40.03 Intersect the cor. of secs. 1 and 12, T. 29 S., R. 1 W.,  
which is a basalt stone, 5x12x10 ins. above ground,  
firmly set, marked and witnessed as described by the  
surveyor general.

Thence N.0\*16'E.

Desc. 530 ft. on NE. slope.

14.80 Creek, 5 lks. wide, course NW.; asc. 410 ft. on SW.  
slope.

35.60 Spur, slope NW.

36.25 Point of intersection with N. bdy. of the Tp., determined  
as hereinafter set forth.

Set a basalt stone, 24x12x8 ins., 18 ins. in the ground,  
for closing cor. of Tps. 28 and 29 S., R. 1 E., marked  
CC on E., with 6 grooves on N., E., and S. faces; from  
which,

A fir, 18 ins. diam., bears N.32\*E., 33 lks.  
dist., mkd. T 28 S R 1 E S 31 C C B T

A fir, 30 ins. diam., bears S.63\*E., 16 lks.  
dist., mkd. T 29 S R 1 E S 6 C C B T

No iron post available for this cor.

The  $\frac{1}{4}$  sec. cor. on E. bdy. of sec. 1, T 29 S., R. 1 W.,  
which is a basalt stone, 5x10x6 ins. above ground,  
firmly set, marked and witnessed as described by the  
surveyor general, bears N.0\*16'E., 3.73 chs. dist.,  
I obliterate marks on bearing tree E. of line, and  
take new bearing tree.