

54
County Surveyor's Record, Douglas County, Oregon

Retracement of Portion of E. Bdy. of T. 29 S., R. 1 E.

CHAINS	
	as described by the surveyor general.
	From the $\frac{1}{4}$ sec. cor.,
	North, retracing line bet. secs. 25 and 30.
	Ascend 25 ft. on S. slope.
3.00	Ridge, divide between South Fork and main South Umpqua River, bears E. and W.; descend 300 ft. on NW. slope, to
20.50	Spur, slopes NW.; descend 70 ft. on NE. slope.
24.00	Bench, bears NW. and SE.
29.90	Creek, 1 lk. wide, course NW.; descend 75 ft. on NW. slope.
36.20	Same creek, course NE.; thence over bench.
39.05	Creek, 2 lks. wide, course NW.; thence over W. slope.
40.20	Fall 8 lks. W. of the cor. of secs. 19, 24, 25 and 30, which is a basalt stone, 4x10x8 ins. above ground, firmly set, marked and witnessed as described by the surveyor general.
	The bearing and length of the south half of this line is N.0°01'W., 39.82 chs.; and of the north half, N.0°07'E., 40.20 chs.
	Land; mountainous.
	Soil; clay loam, stony in places, 2nd and 3rd rate.
	Timber; fir, pine, cedar, and hemlock.
	Undergrowth, laurel, chinquapin, hazel.
Retracement of Subdivision Lines of T. 29 S., R. 1 E.	
	From the cor. of secs. 19, 25, 24, and 30, on E. bdy. of the Tp., heretofore described,
	S.89°43'W., retracing line bet. secs. 24 and 25.
	Over mountainous land, through heavy timber and dense undergrowth.
	Descend 85 ft. on SW. slope.