

Retracement of Subdivision Lines of T. 29 S., R. 1 E.

CHAINS	
	N.89*48'W., retracing line bet. secs. 22 and 27. Over mountainous land, through heavy timber and dense undergrowth. Gradually desc. 50 ft. over N. slope.
17.00	Flat spur, slopes NW.; desc. 210 ft. on W. slope.
27.70	Creek, 1 lk. wide, course NW.; asc. 200 ft. on NE. slope, to
39.98	Fall 8 lks. N. of the $\frac{1}{4}$ sec. cor., which is a conglomerate stone, 4x10x8 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. From the $\frac{1}{4}$ sec. cor., N.89*48'W., retracing line bet. secs. 22 and 27. Gradually asc. 160 ft. on NE. slope.
18.00	Small spur, slopes N.; desc. 400 ft. on NW. slope.
38.00	Foot of descent, on bench, bears NW. and SE.
39.80	Edge of creek bluff, bears NW. and SE.; desc. 10 ft. to
39.89	Fall 24 lks. N. of the cor. of secs. 21, 22, 27 and 28, which is a point on bedrock, 30x15x12 ins. exposed, marked and witnessed as described by the surveyor general, except that the NE. and NW. bearing trees are dead and fallen. I take new bearing trees. From the corner, (New bearing tree) An alder, 8 ins. diam., bears N.89*E., 79 lks. dist., mkd. T 29 S R 1 E S 22 B T (Old bearing tree) A fir, 36 ins. diam., bears S.72*E., 18 lks. dist., mkd. T 29 S R 1 E S 27 B T (Old bearing tree) An alder, 6 ins. diam., bears S.19*W., 42 lks. dist., marked T 29 S R 1 E S 28 B T (New bearing tree) A hemlock, 12 ins. diam., bears N.8*W., 36 lks. dist., mkd. T 29 S R 1 E S 21 B T The bearing and length of the east half of this line is