

58  
County Surveyor's Record, Douglas County, Oregon

Retracement of Subdivision Lines of T. 29 S., R. 1 E.

## CHAINS

N.89°55'W., 39.98 chs.; and of the west half,  
S.89°51'W., 39.89 chs.

Land; mountainous.

Soil; clay loam, stony in places, 2nd and 3rd rate.

Timber; fir, pine, cedar, and hemlock.

Undergrowth; chinquapin, hazel, vine maple, fir.

S.89°59'W., retracing line bet. secs. 21 and 28.

Over mountainous land, through heavy timber and dense  
undergrowth.

Desc. 10 ft. to.

0.25 Creek, 15 lks. wide, course N.; asc. 400 ft. on E.  
slope, to

40.25 Fall 10 lks. S. of the  $\frac{1}{4}$  sec. cor., which is a conglomerate stone, 5x12x12 ins. above ground, firmly set, marked and witnessed as described by the surveyor general, except that the N. bearing tree is dead and fallen. I take new bearing tree.

From the corner,

(New bearing tree) A cedar, 15 ins. diam., bears

N.64°W., 65 lks. dist., mkd.  $\frac{1}{4}$  S 21 B T

(Old bearing tree) A fir, 15 ins. diam., bears

S.44°W., 72 lks. dist., mkd.  $\frac{1}{4}$  S 28 B T

From the  $\frac{1}{4}$  sec. cor.

S.89°59'W., retracing line bet. secs. 21 and 28.

Asc. 240 ft. on E. slope.

28.00 Low flat spur, slopes <sup>N</sup>.; thence nearly level.

40.24 Intersect the cor. of secs. 20, 21, 28 and 29, which is a conglomerate stone, 6x15x8 ins. above ground, firmly set, marked and witnessed as described by the surveyor general.

The bearing and length of the east half of this line is N.89°52'W., 40.25 chs., and of the west half, S.89°59'W., 40.24 chs.