

Retracement and

Resurvey of Subdivision Lines of T. 29 S., R. 1 E.

CHAINS

Land, mountainous.

Soil, clay loam, 2nd and 3rd rate.

Timber, Fir, Cedar, Pine and Hemlock.

Undergrowth, Chinquapin, Fir, Hazel, Snowbrush.

N.89°40'W., retracing line bet. Secs. 20 and 29.

40.33 The ¼ Sec. corner bears S. 14 lks. dist.

81.05 Fall 22 lks. N. of the cor. of Secs. 19, 20, 29 and 30.

The bearing and length of the east half of this line is

N.89°52'W., 40.33 chs; and of the west half,

N.89°47'W., 40.72 chs.

N.89°49'W., retracing line bet. Secs. 19 and 30.

40.07 The ¼ Sec. corner bears S., 6 lks. dist.

79.16 Fall 12 lks. N. of the corner of Secs. 19 and 30 on W.

boundary of the township.

The bearing of this line is N.89°54'W; the length of

the east half is 40.07 chs; and of the west half,

39.09 chs.

From the corner of Secs. 20, 21, 28 and 29.

N.89°52'W., resurveying S. boundary of Sec. 20.

Over mountainous land, through heavy timber and dense undergrowth.

Ascend 210 ft. on E. slope to

19.80 Trail to Dumont Ranger Station, bears NW and SE;

ascend 40 ft. on E. slope.

26.75 Flat spur, slopes N; desc. 170 ft. on W. slope to

40.00 Set a conglomerate stone, 20x8x6 ins., 12 ins. in the ground, for ¼ Sec. corner of Sec. 20 only, marked ¼ on N. face, from which

A Fir, 12 ins. diam., bears N.20°E., 16 lks.

dist., marked ¼ S 20 B T.

A Fir, 6 ins. diam., bears N.13°W., 4 lks.

dist., marked ¼ S 20 B T.