

Resurvey of Subdivision Lines of T. 29 S., R. 1 E.

CHAINS

No iron post available for this corner.

40.33

Intersect the old $\frac{1}{4}$ Sec. corner, which is a conglomerate stone, 5x12x6 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General. Hereafter, this corner will refer to Sec. 29 only. I obliterate marks on bearing tree N. of line, and take new bearing tree; also obliterate marks on N., and mark $\frac{1}{4}$ on S. face of stone, from which

(Old bearing tree) A Fir, 10 ins. diam., bears S.75*E., 7 lks. dist., marked $\frac{1}{4}$ S 29 B T.

(New bearing tree) A Fir, 12 ins. diam., bears S.80*W., 27 lks. dist., marked $\frac{1}{4}$ S 29 B T.

Thence N.89*47'W.

Descend 225 ft. on W. slope.

16.45

Creek, 1 lk. wide, course NW; thence over N. slope.

21.75

Creek, 1 lk. wide, course NE; ascend 20 ft. on E. slope.

23.45

Small spur, slopes N; descend 230 ft. on W. slope.

34.05

Havine, course NW; descend 130 ft. on NW. slope to

39.67

Point 80.00 chs. W. of corner of Secs. 20, 21, 28 and 29.

Set a Basalt stone, 20x18x6 ins., 15 ins. in the ground, for. corner of Secs. 19 and 20, marked with 5 notches on E. edge, from which

A Hemlock, 12 ins. diam., bears N.87*E., 11 lks. dist., marked T 29 S R 1 E S 20 B T.

A Hemlock, 10 ins. diam., bears N.44*W., 26 lks. dist., marked T 29 S R 1 E S 19 B T.

No iron post available for this corner.

Land, mountainous.

Soil, clay loam, stony in places, 2nd and 3rd rate.

Timber, Fir, Hemlock, Cedar and Pine.

Undergrowth, Fir, Chinquapin, Vine Maple, Laurel, Hazel.