

Resurvey of Subdivision Lines of T. 29 S., R. 1 E.

CHAINS

N.89\*47'W., resurveying S. bdy. of sec. 19.

Over mountainous land, through heavy timber and dense undergrowth.

1.05 Intersect the old cor. of secs. 19, 20, 29 and 30, which is a basalt stone, 6x12x6 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. Hereafter, this cor. will refer to secs. 29 and 30 only. I obliterate marks on bearing trees referring to secs. 19 and 20.

From the corner, ( Old bearing trees)

A fir, 6 ins. diam., bears S.75\*E., 6 lks. dist.,  
mkd. T 29 S R 1 E S 29 B T

A fir, 6 ins. diam., bears S.33\*W., 11 lks. dist.,  
mkd. T 29 S R 1 E S 30 B T

Thence N.89\*54'W.

Descend 50 ft. on NW. slope.

2.10 Creek, 8 lks. wide, course NE.; asc. 600 ft. on SE. slope, to

38.95 Point 40.00 chs. W. of the cor. of secs. 19 and 20.

Set a basalt stone, 20x6x6 ins., 15 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 19 only, marked  $\frac{1}{4}$  on N. face; from which

A fir, 10 ins. diam., bears N.62\*E., 36 lks. dist., mkd.  $\frac{1}{4}$  S 19 B T

A fir, 6 ins. diam., bears N.47\*W., 13 lks. dist., mkd.  $\frac{1}{4}$  S 19 B T

No iron post available for this cor.

40.07 Intersect the old  $\frac{1}{4}$  sec. cor., which is a basalt stone, 6x6x6 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. Hereafter, this cor. will refer to sec. 30 only. I obliterate marks on bearing tree N. of line, and take new bearing tree; also obliterate marks on N., and mark  $\frac{1}{4}$  on S. face of stone; from which