

65
County Surveyor's Record, Douglas County, Oregon

10621

Portion of E. Bdy. of Tp., 29 S., R. 1 E.,

CHAINS

North bet. secs. 7 and 12.

Over mountainous land, through heavy timber and dense undergrowth.

Asc. 170 ft. on SE. slope.

5.40 Ridge, divide bet. Buckeye Creek and South Umpqua River, bears NW. and SE.; thence over E. slope.

11.40 Spur, slopes NE.; desc. 460 ft. on NE. slope.

26.20 Spur, slopes NE.; desc. 250 ft. on NW. slope.

34.60 Creek, 2 lks. wide, course NE.; asc. 10 ft. on SE. slope.

35.55 Blazed trail, bears E. and W.; thence over bench, nearly level.

40.00 Set a conglomerate stone, 20x12x6 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; from which,

A pine, 36 ins. diam., bears N.58*E., 19 lks. dist.,
mkd. $\frac{1}{4}$ S 7 B T

A fir, 15 ins. diam., bears N.6*W., 29 lks. dist.,
mkd. $\frac{1}{4}$ S 12 B T

No iron post available for this cor.

Desc. 175 ft. on N. slope.

52.70 Creek, 4 lks. wide, course NW.; asc. 415 ft. on SW. slope.

75.00 Spur, slopes NW.; desc. 20 ft. on NE. slope, to sec. cor.

76.10 Trail to Emerson's, bears NW. and SE.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 1, 6, 7, and 12, with brass cap mkd.

T29S	
R1E	R2E
S1	S6
S12	S7
1921	

from which,

A fir, 12 ins. diam., bears N.83*E., 35 lks. dist.,

mkd. T 29 S R 2 E S 6 B T