

68  
County Surveyor's Record, Douglas County, Oregon

North Bdy. of T. 29 S., R. 1 E.

CHAINS

¼ S 36  
S 1  
1921

from which,

A cedar, 42 ins. diam., bears N.23\*E., 31 lks.  
dist., mkd. ¼ S 36 B T

A fir, 14 ins. diam., bears S.2\*E., 10 lks.  
dist., mkd. ¼ S 1 B T

Asc. 10 ft. on SE. slope.

43.00 Small spur, slopes SW.; desc. 80 ft. on W. slope.

50.10 Quartz Creek, 30 lks. wide, course SE.; asc. 725 ft.  
on NE. slope, to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in  
the ground, for cor. of secs. 1, 2, 35 and 36, with  
brass cap mkd.

T29S | R1E  
S35 | S36  
-----  
S2 | S1  
T29S  
1921

from which,

A fir, 30 ins. diam., bears N.85\*E., 28 lks.  
dist., mkd. T 28 S R 1 E S 36 B T

A fir, 9 ins. diam., bears S.17\*E., 27 lks.  
dist., mkd. T 29 S R 1 E S 1 B T

A chinquapin, 9 ins. diam., bears S.55\*W., 46 lks.  
dist., mkd. T 29 S R 1 E S 2 B T

A fir, 36 ins. diam., bears N.40\*W., 35 lks.  
dist., mkd. T 28 S R 1 E S 35 B T

Land; mountainous, and level.

Soil; in river bottom, alluvial, 1st rate; remainder,  
clay loam, 2nd and 3rd rate.

Timber; fir, cedar, and pine,

Undergrowth; chinquapin, vine maple, fir and hazel.