

72
County Surveyor's Record, Douglas County, Oregon

10629

North Bdy. of T. 29 S., R. 1 E.

CHAINS

West, bet. secs. 5 and 32.

Over mountainous land, through heavy timber and dense undergrowth.

Asc. 350 ft. on E. slope.

16.80 Spur, slopes SE.; desc. 475 ft. on SW. slope, to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ $\frac{S\ 32}{S\ 5}$
1921

from which,

A cedar, 16 ins. diam., bears N.74*E., 34 lks.

dist., mkd. $\frac{1}{4}$ S 32 B T

A fir, 18 ins. diam., bears S.10*W., 13 lks.

dist., mkd. $\frac{1}{4}$ S 5 B T

Desc. 150 ft. on SW. slope.

46.90 Creek, 4 lks. wide, course SE.; asc. 770 ft. on NE. slope.

78.50 Ridge, divide bet. Rock and Boulder Creeks, bears NE.

and SW.; desc. 15 ft. on NW. slope, to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in

the ground, for cor. of secs, 5, 6, 31 and 32,

with brass cap mkd.

T28S | R1E
S31 | S32

S6 | S5
T29S
1921

from which,

A chinquapin, 9 ins. diam., bears N.67*E., 35 lks.

dist., mkd. T 28 S R 1 E S 32 B T

A madrona, 14 ins. diam., bears S.47*E., 79 lks.

dist., mkd. T 29 S R 1 E S 5 B T

A fir, 30 ins. diam., bears S.33*W., 21 lks.

dist., mkd. T 29 S R 1 E S 6 B T

A fir, 24 ins. diam., bears N.37*W., 54 lks.

dist., mkd. T 28 S R 1 E S 31 B T.