

Subdivisions of T. 29 S., R. 1 E.

CHAINS

From the cor. of secs. 23, 24, 25 and 26, heretofore described,

N.0°01'W., bet. secs. 23 and 24.

Over mountainous land, through heavy timber and dense undergrowth.

Ascend 20 ft. on SE. slope.

- 3.00 Spur, slopes NE.; Desc. 50 ft. on N. slope.
- 6.90 Shallow ravine, course NE.; desc. 20 ft. on NE. slope.
- 13.30 Creek, 1 lk. wide, course NE.; asc. 30 ft. on SE. slope.
- 16.35 Small spur, slopes NE.; desc. 130 ft. on NW. slope.
- 25.85 Head of ravine, course NE.; thence over E. slope.
- 34.00 Small spur, slopes NE.; desc. 130 ft. on NW. slope, to
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   
 S 23 | S 24  
 1921

from which,

A hemlock, 18 ins. diam., bears S.46°E., 15 lks.

dist., mkd.  $\frac{1}{4}$  S 24 B T

A yew, 12 ins. diam., bears S.3°W., 24 lks.

dist., mkd.  $\frac{1}{4}$  S 23 B T

Desc. 385 ft. on NW. slope.

- 58.35 Creek, 3 lks. wide, course NE.; desc. 75 ft. on NE. slope.
- 63.35 Same creek, course NW.; thence over W. slope.
- 67.50 Begin descent; 150 ft. on NW. slope.
- 71.60 Same creek, course NE.; descend 85 ft. on NE. slope, to
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 13, 14, 23 and 24, with brass cap mkd.

T29S | R1E  
 S14 | S13  
 S23 | S24  
 1921

from which,