

Subdivisions of T. 29 S., R. 1 E.

CHAINS*

11.40 Spur, slopes SW.; desc. 85 ft. on NW. slope.
 18.20 Ravine, course SW.; asc. 15 ft. on SE. slope.
 20.65 Spur, slopes SW.; desc. 25 ft. on NW. slope.
 23.05 Ravine, course SW.; asc. 170 ft. on SE. slope.
 29.00 Ridge, divide bet. Buckeye Creek and South Umpqua River,
 and blazed trail, bears E. and W.; desc. 300 ft.
 on N. slope.

36.45 Ravine, course NW.; thence over W. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
 S. 11 | S 12
 1921

from which,

A fir, 20 ins. diam., bears S.10*E., 49 lks. dist.,
 mkd. $\frac{1}{4}$ S 12 B T

A fir, 14 ins. diam., bears S.15*W., 31 lks. dist.,
 mkd. $\frac{1}{4}$ S 11 B T

Desc. 40 ft. on NW. slope.

41.70 Ravine, course NW.; asc. 115 ft. on SW. slope.

60.15 Spur, slopes W.; desc. 105 ft. on NW. slope.

69.30 Draw, course W., asc. 200 ft. on SW. slope.

76.30 Spur, slopes NW.; desc. 30 ft. on N. slope, to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in
 the ground, for cor. of secs. 1, 2, 11 and 12, with
 brass cap marked

T29S | R1E
 S2 | S1
 S11 | S12
 1921

from which,

A fir, 24 ins. diam., bears N.66*E., 20 lks. dist.,
 mkd. T 29 S R 1 E S 1 B T

A fir, 18 ins. diam., bears S.17*E., 36 lks. dist.,
 mkd. T 29 S R 1 E S 12 B T