

Subdivisions of T. 29 S., R. 1 E.

CHAINS

From the cor. of secs. 22, 23, 26 and 27, heretofore described,

N.0°02'W., bet. secs. 22 and 23.

Over mountainous land, through heavy timber and dense undergrowth.

Across bench, sloping slightly to W.

0.50 Creek, 1 lk. wide, course NW.

14.00 Leave bench, bears NW. and SE.; asc. 180 ft. on SW. slope.

28.00 Ridge, bears NW. and SE.; desc. 300 ft. on N. slope.

37.25 Ravine, course NE.; desc. 45 ft. on NE. slope, to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4
S 22 | S 23
1921

from which,

A fir, 36 ins. diam., bears S.54°E., 42 lks. dist., mkd. 1/4 S 23 B T

A fir, 20 ins. diam., bears N.18°W., 77 lks. dist., mkd. 1/4 S 22 B T

Desc. 200 ft. on NE. slope.

47.20 Creek, 3 lks. wide, course NW.; asc. 50 ft. on SW. slope.

51.75 Spur, slopes W.; desc. 55 ft. on NW. slope.

55.15 Creek, 2 lks. wide, course W.; asc. 360 ft. on SW. slope.

72.40 Spur, slopes NW.; desc. 450 ft. over bluffs on N. slope.

79.00 Foot of descent, on bench, bears E. and W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 14, 15, 22, and 23, with brass cap marked.

T29S | R1E
S15 | S14

S22 | S23
1921

from which,